



- NOTES:
1. MAXIMUM OPERATING PRESSURE 150 PSIG
 2. MAXIMUM TEMPERATURE 120°F AMBIENT.
 3. RATED INLET FLOW 12 SCFM AT 100 PSIG AT 100°F. OUTLET FLOW 8.8 SCFM AND PURGE FLOW 3.2 SCFM.
 4. ELECTRICAL POWER 230V/150/60
 5. POWER CORD SUPPLIED
 6. DRYER WEIGHT 11 LBS
 7. DRYER IS DESIGNED TO BE WALL OR BULKHEAD MOUNTED. OPTIONAL FLOOR STAND KIT AVAILABLE PN 50-0150.
 8. POWER CORD AND SOLENOID VALVE POWER CABLES NOT SHOWN.

PT# 81-2338

THIS DRAWING IS THE PROPERTY OF
VAN AIR INC.

AND IS SUBJECT TO RETURN UPON REQUEST. IT SHALL NOT BE COPIED OR DUPLICATED IN ANY MANNER AND SHALL NOT BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT THE CONSENT OF VAN AIR INC. IT SHALL BE USED FOR REFERENCE TO WORK UNDER CONTRACT OR PROPOSALS SUBMITTED BY VAN AIR INC. ONLY.

MINI HEATLESS REGENERATIVE DRYER
MHL12-230

DRWN BY: JMY	DATE: 10-10-07	DRWG No.	REV
CHECKED:	SCALE: NONE	SD-14310	

APP'L: **VAN AIR SYSTEMS**

A DIVISION OF **VAN AIR INC.** LAKE CITY, PA 16423 (814)774-2631 FAX:(814)774-4065